



Shubham Pack®



SPM-300 L/P

For Viscous Liquid
and Powder Products



SPM-300 L/P

For Viscous Liquid & Powder Products



SPECIFICATIONS

Sealing Style	4 Side Seal
Speed	40 - 60 Strokes / minutes (Depends upon the type of product & quantity to be filled)
No. of Tracks	Depends upon the width of the pouch
Laminate Specification	Roll Width 300 mm max. Roll Dia 350 mm. max. Reel Core I.D. 76 mm.
Max. Length of Pouch	160 mm.
Packing Material	Laminates with one side heat sealable
Filling Capacity	Powder 5g - 100g Liquid 1ml - 100 ml
Product To Be Packed	Powder & Liquids / Pastes within dosable viscosity range
Sealing Drives	Pneumatic Operated
Filling Mechanism	Powder : Auger Filler / Volumetric Cup Filler Liquid : Piston Filler / Solenoid Valve Filling System
Sealing Type	Plain / Line / Serration
Perforation and Cutting	Zig Zag Perforation
Laminate Roll Unwind	Through Dancing Roller
Laminate Draw Off System	Through Clutch Brake / Servo Driven
Control Panel	Air Cooled with all applicable standards
Contact Parts	SS 304 / SS 316 L
Batch Cutter Operation	Pneumatic Operated
Mat Format	As per Requirement
Electrical Spec.	3 Phase, 415 V, 50/60 Hz
Layout Dimensions	Length 2000 mm Width 1000 mm Height 1900 mm
Machine Weight	Net Weight 1200 kgs. Gross weight 1500 kgs.
Air Compressor	5 CFM @ 6 Bar (Compressor is not in the scope of supply)
Power Consumption	6 - 8 KW Approx.
Scrap Rate	Less than 1%*
Machine Color	Shell Grey - Powder coated.
Weight Variation	Within +/- 1%** of the filled quantity
Temp Controller	PID Based
Embossing Provision	Provision Given (Digits not included)

Corporate Office and Works: B-8A, Sector 59 Part II, Ballabgarh, Faridabad - 121004, Haryana (India)

Mobile: +91 813 019 2000/2001

Phone: +91 129 42 723 50/51/52/53/54/55

E-mail : marketing@shubhampack.com, ccare@shubhampack.com
export@shubhampack.com, shubham@shubhampack.com